

## NOTES:

- 1. Specific site conditions may require an increase in concrete encasement dimensions and/or reinforcement. It is the customer's responsibility to ensure the concrete encasement is designed for the application. A minimum concrete strength of 25MPa is recommended. The concrete should be vibrated to eliminate air pockets. *Engineering advice may be required*.
- 2. The finished level of the asphalt must be approx. 3mm above the top of the channel edge.
- 3. Haunch slopes away at ratio 1:4, or approx 15°.
- 4. Refer to ACO's latest installation instructions for complete details

# SPECIFICATION CLAUSE MINIKLASSIK M50KS - LOAD CLASS C-D

#### GENERA

THE SURFACE DRAINAGE SYSTEM SHALL BE ACO'S MINIKLASSIK M50KS POLYMER CONCRETE MINI CHANNEL SYSTEM WITH STAINLESS STEEL EDGE RAILS AS MANUFACTURED BY ACO.

## MATERIALS

M50KS CHANNELS SHALL BE MANUFACTURED FROM POLYESTER RESIN POLYMER CONCRETE WITH INTEGRALLY CAST-IN STAINLESS STEEL EDGE RAILS. PROPERTIES OF POLYMER CONCRETE WILL BE AS FOLLOWS WITH SUPPORTING DOCUMENTATION:

COMPRESSIVE STRENGTH:	98 MPa
FLEXURAL STRENGTH:	26 MPa
TENSILE STRENGTH:	14 MPa
WATER ABSORPTION:	0.07%
FROST PROOF:	YES
COEFFICIENT OF EXPANSION/CONTRACTION:	2.02x10 <sup>-5</sup> /°C
WATER VAPOUR TRANSMISSION:	0.0364g/m <sup>2</sup>
NON FLAMMABLE:	YES
COEFFICIENT OF ROUGHNESS (MANNINGS):	n=0.011
RESISTANT TO WEATHERING:	YES
DILUTE ACID AND ALKALI RESISTANT:	YES
SF SEALANT GROOVE	YES

#### CHANNELS

M50KS CHANNEL SHALL BE 50mm NOMINAL INTERNAL WIDTH WITH AN OVERALL WIDTH OF 80mm. CHANNELS SHALL HAVE AN OVERALL DEPTH OF 89mm FOR USE IN COMPACT AREAS. ALL CHANNELS SHALL BE INTERLOCKING WITH A MALE/FEMALE JOINT.

#### RATES

INSERT SPECIFICATION FOR THE SELECTED GRATE. REFER TO THE RELEVANT ACO SPECIFICATION INFORMATION SHEET, CLICK www.acodrain.com.au/resources.

# INSTALLATION

THE COMPLETE DRAINAGE SYSTEM SHALL BE BY ACO AND TO BE INSTALLED FOR ITS INTENDED PURPOSE. ANY DEVIATION OR PARTIAL USE OF THE SPECIFIED SYSTEM AND/OR IMPROPER INSTALLATION WILL VOID ALL WARRANTIES PROVIDED BY ACO.

M50KS-CD-A1

**ACO**DATE: 03/14

M50KS - MINIKLASSIK - LOAD CLASS: C-D

**INSTALLATION DRAWING - ACO DRAIN** 

ACO Polycrete Pty Ltd Australia Ph: 1300 765 226 www.acodrain.com.au ACO Limited New Zealand Ph: 0800 448 080 www.acodrain.co.nz