




This grate is part of ACO's Heelsafe® Anti-Slip range. For more information visit www.heelsafe.com.au

Product Features

- Certified to AS 3996 Load Class B (80kN) (NATA endorsed load test reports available)
- AS 3996 (Clause 3.3.5) compliant for surface openings in pedestrian areas
ASME A112.6.3 (Section 7.12) compliant - American high heel standard
- AS 4586: P3 – Slip resistance classification for Wet Pendulum Test
AS 4586: C/B¹ - Slip resistance classification for Wet-Barefoot Inclining Platform Test
AS 4586: R10/R10¹ - Slip resistance classification for Oil-Wet Inclining Platform Test
- AS 1428.2 (Clause 9c) compliant for wheelchair and walking cane safety
- AS 3996 (Clause 3.3.6) compliant for bicycle tyre penetration resistance
 - Raised mechanical nodes for tread durability
 - No end bars for visual continuity
 - **QuickLok** boltless locking system
 - Suitable for use with K300, KS300, H300K, H300KS channels
 - Manufactured from Grade 304 stainless steel

¹ Test direction (perpendicular/parallel) relative to the grate's length (NATA endorsed test reports available)



Specifications

The grate shall be ACO Type 847Q Stainless Wedgewire Heelsafe® Anti-Slip grate with QuickLok boltless locking system as manufactured by ACO. This grate has an overall width of 338mm and overall length of 1000mm (Type 847Q) and 500mm (Type 848Q). Slot widths measure at a maximum of 6mm.

Materials & Design

The grate shall be manufactured from stainless steel and have minimum properties and characteristics as follows:

- Raised mechanical nodes for tread durability
- No end bars for visual continuity
- Manufactured from Grade 304 stainless steel
- Certified to AS 3996 Load Class B (80kN)²
- AS 4586: P3 – Slip resistance classification for Wet Pendulum Test²
- AS 4586: C/B¹ - Slip resistance classification for Wet-Barefoot Inclining Platform Test²
- AS 4586: R10/R10¹ – Slip resistance classification for Oil-Wet Inclining Platform Test²
- Meets AS 1428.2 (Clause 9c); AS 3996 (Clause 3.3.5 & 3.3.6); ASME A112.6.3 (Section 7.12)
- Intake area of 169,775mm² per metre of grate/84,890mm² per half metre of grate

¹ Test direction (perpendicular/parallel) relative to the grate's length

² NATA endorsed test reports available


For the specification of the ACO Drain channel system selected, click: <http://www.acodrain.com.au/resources>

ACO Specification Information




ACO DRAIN®

Type 847Q/848Q Stainless Wedgewire Heelsafe® Anti-Slip grate



Description	Part No.	Length (mm)	Width (mm)	Weight (kg)
QuickLok grate				
Type 847Q Stainless Wedgewire Heelsafe® Anti-Slip	98975	1000	338	12.5
Type 848Q Stainless Wedgewire Heelsafe® Anti-Slip	98995	500	338	6.2
QuickLok locking bar	10458	-	-	0.1
Grate removal tool	01318	-	-	0.1

QuickLok locking mechanism



ACO **QuickLok** is a patented boltless locking system, grates are removed and replaced with the minimum time and effort for ease of maintenance. The unique design provides a positive 'snap down' fit into the locking bar. A spigot is fixed to the grate which 'locks' into the spring in the locking bar.

The **QuickLok** spigot is manufactured from stainless steel and high density nylon, the locking bar and spring are stainless steel, for use in both general purpose and corrosive environments.

ACO Polycrete Pty Ltd
Australia

Ph: 1300 765 226
www.acodrain.com.au
sales@acoaus.com.au

ACO Limited
New Zealand

Ph: 0800 448 080
www.acodrain.co.nz
sales@aconz.co.nz



© February, 2014 ACO Polycrete Pty Ltd. All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions are suitable. ACO Polycrete Pty Ltd. pursues a policy of continuous product development and reserves the right to amend specifications without notice.