

**Product Features**



Certified to AS 3996 Load Class D (210kN)  
(NATA endorsed load test reports available)



AS 3996 (Clause 3.3.6) compliant for bicycle tyre penetration resistance

- Recesses in the edge rail fit around 'anti-shunt' lugs on the grate to prevent longitudinal movement
- **QuickLok** boltless locking system
- Suitable for use with K300, KS300, H300K, H300KS channels
- Manufactured from either galvanised steel or Grade 304 stainless steel
- Galvanised steel for use in general purpose applications (pictured)
- Stainless steel with electropolish finish for aesthetics and/or its corrosion resistant properties



**Specifications**

The grate shall be ACO Type 805Q/830Q\* Galvanised/Stainless\* Mesh grate with **QuickLok** boltless locking system as manufactured by ACO. This grate has an overall width of 338mm and overall length of 500mm. Slot widths measure at a maximum of 17mm.

**Materials & Design**

The grate shall be manufactured from galvanised/stainless\* steel and have **minimum** properties and characteristics as follows:

- Recesses in the edge rail fit around 'anti-shunt' lugs on the grate to prevent longitudinal movement
- Manufactured from galvanised/electropolish Grade 304 stainless\* steel
- Certified to AS 3996 Load Class D (210kN)<sup>1</sup>
- Meets AS 3996 (Clause 3.3.6)
- Intake area of 110,910mm<sup>2</sup> per half metre of grate

<sup>1</sup> NATA endorsed test reports available

For the specification of the ACO Drain channel system selected, click: <http://www.acodrain.com.au/resources>


\*delete as appropriate

**ACO DRAIN®**


**Type 805Q/830Q Steel Mesh grate**



**Plan view**




**Side elevation**



Description	Part No.	Length (mm)	Width (mm)	Weight (kg)
<b>QuickLok grate</b>				
Type 805Q Galvanised Mesh	141743	500	338	12.7
Type 830Q Stainless Mesh	141748	500	338	15.1
<b>QuickLok locking bar</b>	10458	-	-	0.1
Grate removal tool	01318	-	-	0.1

**QuickLok locking mechanism**



ACO **QuickLok** is a patented boltless locking system, grates are removed and replaced with the minimum time and effort for ease of maintenance. The unique design provides a positive 'snap down' fit into the locking bar. A spigot is fixed to the grate which 'locks' into the spring in the locking bar.

The **QuickLok** spigot is manufactured from stainless steel and high density nylon, the locking bar and spring are stainless steel, for use in both general purpose and corrosive environments.

**ACO Polycrete Pty Ltd Australia**

Ph: 1300 765 226  
www.acodrain.com.au  
sales@acoaus.com.au

**ACO Limited New Zealand**

Ph: 0800 448 080  
www.acodrain.co.nz  
sales@aconz.co.nz



© August, 2016 ACO Polycrete Pty Ltd. All reasonable care has been taken in compiling the information in this document. All recommendations and suggestions on the use of ACO products are made without guarantee since the conditions of use are beyond the control of the company. It is the customer's responsibility to ensure that each product is fit for its intended purpose and that the actual conditions are suitable. ACO Polycrete Pty Ltd. pursues a policy of continuous product development and reserves the right to amend specifications without notice.